

**SECTION 11110****TUMBLE DRYER, 35 LB. (15.9 KG) CAPACITY****PART 1 GENERAL**

## 1.01 SECTION INCLUDES:

- A. Automatic laundry dryer for processing water-washed linen items

## 1.02 SYSTEM DESCRIPTION

## A. DESIGN REQUIREMENTS:

- 1. Dry weight capacity: 35 lb. (15.9 kg)
- 2. Cylinder volume: 12.27 cu ft (347448 cu cm) minimum
- 3. Construction: Heavy duty embossed steel with e-coat and baked enamel powder paint
- 4. Input voltage: 240/60/3
- 5. Heat source: Electric, 24 kW
- 6. Overall width: 31-1/2 inches (800 mm) nominal
- 7. Overall height: 63-7/8 inches (1622 mm) nominal
- 8. Overall depth: 46-7/8 inches (1191 mm) nominal
- 9. Exhaust size: 8 inch (203 mm)
- 10. Control system: Microprocessor touchpad control
- 11. Stainless steel door: High grade stainless steel door with 7/8 inch (22 mm) rubber gasket and heavy duty hinge

## B. PERFORMANCE REQUIREMENTS:

- 1. Airflow: 650 CFM (18.4 CMM)
- 2. Motor horsepower: 1/4 hp cylinder and 1/4 hp fan
- 3. Control system
  - a. minimum of eight automatic drying cycles
  - b. ability to time dry
  - c. variable temperature settings from 120 - 180°F (49 - 82°C)
  - d. wrinkle free at cycle end allowing 2-1/2 minutes of tumble and 2-1/2 minutes of rest until door opens or maximum of one hour
- 4. Lint filter: 480 sq. inch (3097 sq. cm), self cleaning, depositing lint to large storage area at bottom of tumbler

## 1.03 DELIVERY, STORAGE &amp; HANDLING

## A. ACCEPTANCE AT SITE:

- 1. Inspect machine for damage prior to acceptance. If damage is found, follow freight handler's procedure for claims.

## B. STORAGE &amp; PROTECTION

- 1. Machine should be stored in a site protected from weather, direct sunlight & temperature extremes. Do not remove packaging prior to storage.
- 2. If machine is to be stored for an extended period of time, consult manufacturer for special requirements.

1.04 WARRANTY

- A. Warranty Period: Three years, limited, parts only, commencing on Date of Substantial completion

1.05 SYSTEM STARTUP & COMMISSIONING

- A. Machine installation should be inspected by local manufacturer's representative prior to startup & operation. The party installing the machine is responsible for setting the schedule for this inspection.

**PART 2 PRODUCTS**

- A. Source quality
- B. Alliance Laundry Systems LLC - UniMac, obtain commercial laundry equipment from a single manufacturer

1.02 QUALIFIED MODELS

- A. UniMac model **UT035EOM** (no substitutions permitted)

**PART 3 EXECUTION**

1.01 INSTALLATION

- A. Refer to & comply with manufacturer's installation instructions. Do not deviate without permission from site owner, architect, general contractor & manufacturer's local representative.