



## On-Premises Hardmount Washer-Extractors

### **Value Line** **M30 Control**



A 5-year limited warranty is issued on the frame, basket, shaft, bearings and seals if failure or breakage should occur during normal operation due to defects in material or workmanship that would prohibit its further use. A full 3-year warranty also is issued to the original purchaser on all parts. Labor not included.



### **UniMac's Value Line is high in quality, low in price.**

When you need good quality, highly reliable laundry equipment, our mid-featured Value Line will fit your budget. This group of washer-extractors uses the same A-frame design as our premium high performance models. It also offers the same industry-leading three and five-year limited parts warranties. UniMac's Value Line cuts no corners in reliability!

#### **M30 Control Features**

- 30 Programmable Cycles
- Three ways to program (manual, PDA or laptop)
- Real Time Clock to record events by date and time
- 30 Programmable Water Levels to manage water consumption
- Cylinder Rotation Sensor
- Eight Max Fill Segments
- Temperature Controlled Fill
- Auto Leak Detection to manage water consumption
- Wet Clean Capable with 1/2 speed wash
- Wash Actions Programmable in wide-range from delicate to heavy soil
- Diagnostic capabilities
- Four Supply Signals

#### **Standard Features**

- **Fill Valves**  
The two brass fill valves are the same high quality components used in our premium models.
- **Supply Dispenser**  
The Value Line offers four liquid signals for automated dispensing. It also can be used as a dry supply dispenser with five flushing compartments.

**Expert Solutions from the Laundry Experts**

# Specifications

	UW35 M30			UW60 M30			UW80 M30	UW100 M30	UW125 M30	
Capacity - lb (kg)	35 (15.9)			60 (27.3)			80 (36.4)	100 (45.5)	125 (56.9)	
Width - in (mm)	33 3/8" (848)			36 5/8" (930)			41 1/2" (1054)	41 1/2" (1054)	48" (1219)	
Depth - in (mm)	43 5/8" (1108)			45" (1143)			51 1/2" (1308)	54 1/2" (1384)	58" (1473)	
Height - in (mm)	55 1/2" (1410)			64 1/2" (1638)			68 1/2" (1740)	68 1/2" (1740)	72" (1829)	
Cylinder Diameter - in (mm)	26 1/4" (667)			32" (813)			36" (914)	36" (914)	42" (1067)	
Cylinder Depth - in (mm)	18 3/8" (467)			20" (508)			21" (533)	27" (686)	24" (610)	
Cylinder Volume - cu. ft. (liters)	5.76 (163)			9.31 (264)			12.4 (350)	15.9 (450)	19.4 (544)	
Door Opening - in (mm)	14 3/8" (364)			17 1/2" (445)			17 1/2" (445)	17 1/2" (445)	20" (508)	
Door Bottom to Floor - in (mm)	23 3/4" (603)			28 1/4" (718)			29" (737)	29" (737)	29" (737)	
Water Inlet Connection - in (mm)	3/4" (19)			3/4" (19)			3/4" (19)	3/4" (19)	(2 ea) 1" (25)	
Steam Connection - in (mm)	1/2" (13)			1/2" (13)			1/2" (13)	1/2" (13)	3/4" (19)	
Drain Diameter - in (mm)	2.4" (60)			3" (76)			3" (76)	3" (76)	3" (76)	
	2 Sp	L Sp	M Sp	2 Sp	L Sp	M Sp	M Sp	M Sp	M Sp	
Motor Size - HP (kW)	2.0 (1.5)	5.0 (3.7)	5.0 (3.7)	3.0 (2.2)	5.0 (3.7)	5.0 (3.7)	7.5 (5.6)	7.5 (5.6)	10 (7.5)	
Cylinder Speed RPM (G-Force)	Wash	50 (.95)	44 (0.7)	44 (0.7)	44 (.88)	40 (0.7)	40 (0.7)	40 (0.8)	40 (0.8)	37 (0.8)
	Distribution	-	83 (2.6)	83 (2.6)	-	71 (2.3)	71 (2.3)	70 (2.5)	70 (2.50)	62 (2.29)
	Very Low Extract	-	401 (60)	401 (60)	-	364 (60)	364 (60)	343 (60)	343 (60)	317 (60)
	Low Extract	-	518 (100)	568 (120)	-	469 (100)	514 (120)	485 (120)	485 (120)	449 (120)
	Medium Extract	-	-	695 (180)	-	-	630 (180)	594 (180)	594 (180)	550 (180)
High Extract	504 (95)	-	-	465 (98)	-	-	-	-	-	
Domestic Shipping Dimensions - in (mm)	Width	38" (970)	38" (970)	38" (970)	40" (1016)	40" (1016)	40" (1016)	44" (1118)	44" (1118)	61 1/2" (1560)
	Depth	47" (1200)	47" (1200)	47" (1200)	49" (1245)	49" (1245)	49" (1245)	60 1/2" (1537)	60 1/2" (1537)	60" (1520)
	Height	64" (1630)	64" (1630)	64" (1630)	74 1/2" (1892)	74 1/2" (1892)	74 1/2" (1892)	77 1/4" (1962)	77 1/4" (1962)	77 3/4" (1980)
Domestic Net Weight - lb (kg)	750 (341)	750 (341)	1030 (468)	1136 (515)	1229 (557)	1300 (590)	1644 (747)	1680 (762)	2211 (1005)	
Domestic Shipping Weight - lb (kg)	810 (367)	810 (367)	1085 (493)	1175 (533)	1268 (575)	1340 (608)	1705 (773)	1745 (792)	2525 (1148)	
Export Shipping Weight - lb (kg)	910 (413)	910 (413)	1150 (522)	1300 (590)	1392 (631)	1464 (664)	1990 (903)	2030 (921)	2800 (1270)	
Agency Approvals*	cETLus, CE			cETLus, CE			cETLus, CE	cETLus, CE	cETLus, CE	

\* Agency approvals may vary depending on configuration. Consult factory for details.

For electrical specifications, circuit breaker requirements and full load amperages, see your authorized UniMac distributor. Manufacturer strongly recommends using a circuit breaker instead of fuses. Use 3-pole circuit breakers for 3-phase machines.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2000.

©Copyright 2009 Alliance Laundry Systems LLC

**No wonder UniMac is America's No. 1 selling brand!**

[www.unimac.com](http://www.unimac.com)

Alliance Laundry Systems  
Shepard Street, Ripon, WI 54971 Telephone: 1-800-587-5458

